



Końcówki typ CN

obrázek	index (pozinkovaná ocel)	vnitř. průměr koncovky [coul]	vnitř. průměr koncovky [mm]	rozsah vnějších průměrů hadice [mm]	vnitř. průměr objímky [mm]	délka objímky [mm]
Lisovací objímka pro hadice typ CNFH (HEAVY DUTY) 	AC-CNFH-200A	2	51	63,5 ÷ 67	69,9	88,9
	AC-CNFH-200B	2	51	67 ÷ 73	76,2	88,9
	AC-CNFH-200C	2	51	73 ÷ 79	82,5	88,9
	AC-CNFH-250A	2.1/2	63	76 ÷ 79	82,5	108
	AC-CNFH-250B	2.1/2	63	79 ÷ 92	95,2	108
	AC-CNFH-300A	3	76	89 ÷ 92	95,2	127
	AC-CNFH-300B	3	76	92 ÷ 98	101,6	127
	AC-CNFH-300C	3	76	98 ÷ 102	104,8	127
	AC-CNFH-300D	3	76	102 ÷ 105	108	127
	AC-CNFH-300E	3	76	105 ÷ 108	114,3	127
	AC-CNFH-400A	4	102	114 ÷ 121	123,8	139,7
	AC-CNFH-400B	4	102	121 ÷ 125	128,6	139,7
	AC-CNFH-400C	4	102	125 ÷ 128	131,8	139,7
	AC-CNFH-400D	4	102	128 ÷ 132	134,9	139,7
	AC-CNFH-400E	4	102	133 ÷ 136	139,7	139,7
	AC-CNFH-400F	4	102	133 ÷ 140	142,9	139,7
	AC-CNFH-500A	5	127	146 ÷ 152	155,6	174,6
	AC-CNFH-500B	5	127	152 ÷ 162	165,1	178,3
	AC-CNFH-600A	6	152	171 ÷ 181	184,1	190,5
	AC-CNFH-600B	6	152	181 ÷ 187	190,5	190,5
	AC-CNFH-600C	6	152	187 ÷ 192	195,3	190,5
	AC-CNFH-600D	6	152	194 ÷ 203	206,4	190,5
	AC-CNFH-800A	8	204	229 ÷ 238	241,3	215,9
	AC-CNFH-800B	8	204	240 ÷ 257	260,3	215,9

obrázek	index (pozinkovaná ocel)	vnitř. průměr koncovky [coul]	vnitř. průměr koncovky [mm]	rozsah vnějších průměrů hadice [mm]	vnitř. průměr objímky [mm]	délka objímky [mm]
Lisovací objímka pro hadice typ CNFL 	AC-CNFL-150-1	1.1/2	38	49 ÷ 51	53,8	74
	AC-CNFL-150-2	1.1/2	38	51 ÷ 54	56,9	74
	AC-CNFL-150-3	1.1/2	38	54 ÷ 57	60	74
	AC-CNFL-200-1	2	51	65 ÷ 67	70	90
	AC-CNFL-200-2	2	51	67 ÷ 70	73	90
	AC-CNFL-200-3	2	51	70 ÷ 73	76,2	90
	AC-CNFL-250-1	2.1/2	63	78 ÷ 82,5	82,3	89
	AC-CNFL-250-2	2.1/2	63	80 ÷ 82,5	85,1	89
	AC-CNFL-300-1	3	76	90,5 ÷ 92	94,5	117
	AC-CNFL-300-2	3	76	92,5 ÷ 95	98	117
	AC-CNFL-300-3	3	76	95,5 ÷ 98,5	100	117
	AC-CNFL-400-1	4	102	117,5 ÷ 119	124	135
	AC-CNFL-400-2	4	102	119,5 ÷ 122	128	135
	AC-CNFL-400-3	4	102	122,5 ÷ 125,5	130	135