

Závítové spojky z nerez 316

Redukce, vnější / vnitřní kuželový závít				
  62080				
index	rozměr závitu 1 (BSPT)	rozměr závitu 2 (BSP)	délka [mm]	rozměr klíče [mm]
AI-62080-04-02	1/4"	1/8"	16	14
AI-62080-06-02	3/8"	1/8"	16,5	17
AI-62080-06-04	3/8"	1/4"	16,5	17
AI-62080-08-04	1/2"	1/4"	19,5	22
AI-62080-08-06	1/2"	3/8"	19,5	22
AI-62080-12-08	3/4"	1/2"	23,5	27

Redukční mufna, vnitřní závít				
  62310				
index	rozměr závitu 1 (BSP)	rozměr závitu 2 (BSP)	délka [mm]	rozměr klíče [mm]
AI-62310-02-04	1/8"	1/4"	19	17
AI-62310-04-06	1/4"	3/8"	23	22
AI-62310-06-08	3/8"	1/2"	27,5	24
AI-62310-08-12	1/2"	3/4"	30	30
AI-62310-02-04	1/8"	1/4"	19	17

Zátka, vnější závít* (kulatá, imbus) o-ring viton			
  62315			
index	rozměr závitu (BSP, metrický)	délka [mm]	rozměr klíče [mm]
AI-62315-M5	M5	6	2
AI-62315-02	1/8"	8,5	5
AI-62315-04	1/4"	11	6
AI-62315-06	3/8"	12,5	8
AI-62315-08	1/2"	13,5	10

* Pracovní teplota: Od -15°C do +200°C

Zátka, vnější závít (šestihran)			
  62320			
index	rozměr závitu (BSP)	délka [mm]	rozměr klíče [mm]
AI-62320-02	1/8"	10	14
AI-62320-04	1/4"	13	17
AI-62320-06	3/8"	13,5	19
AI-62320-08	1/2"	14,5	24
AI-62320-12	3/4"	16	30

Zátka, vnější kuželový závít (kulatá, imbus, DIN 906)			
  62325			
index	rozměr závitu (BSPT)	délka [mm]	rozměr klíče [mm]
AI-62325-02	1/8"	7,5	5
AI-62325-04	1/4"	10	6
AI-62325-06	3/8"	11	8
AI-62325-08	1/2"	13	10

Tlumič, vnější závít*				
  62540				
index	rozměr závitu (BSP)	hlučnost při 6 bar [dB]	délka [mm]	rozměr klíče [mm]
AI-62540-02	1/8"	73	15	14
AI-62540-04	1/4"	74	15	17
AI-62540-06	3/8"	86	18	22
AI-62540-08	1/2"	80	22	27

* Pracovní teplota: od -20°C do +300°C

Tlak: 10 bar

Stupeň filtrace: 70 µm