

AirTac Série G



Filtr – regulátor GFR

Rozměr:	200, 300, 400, 600
Rozsah výst. tlaku:	0÷9 bar
Stupeň filtrace:	40 µm
Přívodní tlak:	Do 10 bar
Prac. teplota:	Do +70°C
Přípojky:	GW BSP 1/8" ÷ 1"
Odvod kond.:	Automatický (A)
Průtok:	2100 l/min - 200 3800 l/min - 300 6750 l/min - 400 11100 l/min - 600 (při vst. tlaku 6 bar a Δp = 1 bar)

200	300	400	600	přípojky
AT-GFR200-06				1/8"
AT-GFR200-08	AT-GFR300-08			1/4"
	AT-GFR300-10	AT-GFR400-10		3/8"
	AT-GFR300-15	AT-GFR400-15		1/2"
			AT-GFR600-20	3/4"
			AT-GFR600-25	1"

V kompletu montážní úchyt a manometr.



Maznice GL

Rozměr:	200, 300, 400, 600
Objem zásobníku:	25 cm ³ – série 200 75 cm ³ – série 300 160 cm ³ – série 400 380 cm ³ – série 600
Přívodní tlak:	Do 10 bar
Prac. teplota:	Do +70°C
Přípojky:	GW BSP 1/8" ÷ 1"
Průtok:	3200 l/min - 200 5400 l/min - 300 8300 l/min - 400 12000 l/min - 600 (při vst. tlaku 6 bar a Δp = 1 bar)

200	300	400	600	přípojky
AT-GL200-06				1/8"
AT-GL200-08	AT-GL300-08			1/4"
	AT-GL300-10	AT-GL400-10		3/8"
	AT-GL300-15	AT-GL400-15		1/2"
			AT-GL600-20	3/4"
			AT-GL600-25	1"

V kompletu montážní úchyt.