






Rychlospojky ISO-A



Spojka PUSH PULL 	rozměr [coul]	rozměr závitu [coul]	index	
			DNP	HOLMBURY
	1/2	GW 1/2 BSP	DP-PPV1-1313002	HQ-IA12P-F-08G
				HQ-IA12CP-F-08G*

spojka s eliminátorem tlaku

Spojka PUSH PULL (DIN 2353) 	rozměr [coul]	rozměr závitu [mm]	index	
			DNP	HOLMBURY
	1/4	M14x1,5 (8L)	DP-PPV3-0614302	-
	3/8	M16x1,5 (10L)	DP-PPV3-1016302	-
		M18x1,5 (10S)	DP-PPV3-1018402	-
	1/2	M18x1,5 (12L)	DP-PPV3-1318302	HQ-IA12P-F-12L
		M22x1,5 (15L)	DP-PPV3-1322302	HQ-IA12P-F-15L
		M22x1,5 (14S)	DP-PPV3-1322402	-
		M24x1,5 (16S)	DP-PPV3-1324402	-
	3/4	M30x2 (22L)	DP-PPV3-2030302	-
		M30x2 (20S)	DP-PPV3-2030402	-
	1	M36x2 (28L)	DP-PPV3-2536302	-
		M42x2 (30S)	DP-PPV3-2542402	-

Spojka PUSH PULL (přepážková verze DIN 2353) 	rozměr [coul]	rozměr závitu [mm]	index	
			DNP	HOLMBURY
	1/2	M18x1,5 (12L)	DP-PPV3-1318502	HQ-IA12P-F-12L-B
		M22x1,5 (15L)	DP-PPV3-1322502	HQ-IA12P-F-15L-B

Záslepka spojky 	rozměr [coul]	materiál	index	
			DNP	HOLMBURY
	1/4	PVC	DP-SPAV-06002	HQ-IA06-F-RED
	3/8		DP-SPAV-10002	HQ-IA10-F-RED
	1/2		DP-SPAV-13002	HQ-IA12-F-RED
	3/4		DP-SPAV-20002	HQ-IA19-F-RED
	1	hliník	DP-SPAV-25002	HQ-IA25-F-RED
	1.1/4		DP-SPAV-30202	-
	1.1/2		DP-SPAV-39202	-
	2		DP-SPAV-50202	-

Záslepka vsuvky 	rozměr [coul]	materiál	index	
			DNP	HOLMBURY
	1/4	PVC	DP-SPAV-06003	HQ-IA06-M-RED
	3/8		DP-SPAV-10003	HQ-IA10-M-RED
	1/2		DP-SPAV-13003	HQ-IA12-M-RED
	3/4		DP-SPAV-20003	HQ-IA19-M-RED
	1	hliník	DP-SPAV-25003	HQ-IA25-M-RED
	1.1/4		DP-SPAV-30203	-
	1.1/2		DP-SPAV-39203	-
	2		DP-SPAV-50203	-

Pracovní parametry

rozměr [coul]	pracovní tlak [bar]		průtok při $\Delta p = 3$ bar [l/min]	
	DNP	HOLMBURY	DNP	HOLMBURY
1/4	350	400	13	13
3/8	350	350	70	49
1/2	250	320	88	108
3/4	250	300	168	147
1	200	250	236	325
1.1/4	200	250	413	518
1.1/2	190	230	595	705
2	160	170	1341	1231