






Rychlospojky DYROS - série 6, 90, 80

Vsvuka s vnějším závitem L=100 mm 	index (s ventilem)	index (bez ventilu)	série	rozměr závitu	světlost [mm]
	-	DY-N610-100	6	M10x1	6
	-	DY-N645-100		M14x1,5	6
	-	DY-N618-100		1/8" BSP	6
	-	DY-N614-100		1/4" BSP	6
	-	DY-N638-100		3/8" BSP	6
	-	DY-N918-100	90	1/8" BSP	9
	-	DY-N914-100		1/4" BSP	9
	-	DY-N938-100		3/8" BSP	9
	-	DY-N945-100		M14x1,5	9
-	DY-N965-100	M16x1,5		9	

Vsvuka s vnitřním závitem 	index (s ventilem)	index (bez ventilu)	série	rozměr závitu	světlost [mm]	L [mm]
	-	DY-NI618	6	1/8" BSP	6	28
	-	DY-NI614		1/4" BSP	6	28
	-	DY-NI918	90	1/8" BSP	9	27
	-	DY-NI914		1/4" BSP	9	27
	-	DY-NI938		3/8" BSP	9	27
-	DY-NI912	1/2" BSP		9	28	

Vsvuka 90° s vnějším závitem 	index (s ventilem)	index (bez ventilu)	série	rozměr závitu	světlost [mm]	L [mm]
	-	DY-VN610	6	M10x1	6	29
	-	DY-VN645		M14x1,5	6	29
	-	DY-VN618		1/8" BSP	6	29
	-	DY-VN614		1/4" BSP	6	29
	-	DY-VN638		3/8" BSP	6	29
	-	DY-VN914	90	1/4" BSP	9	33
	-	DY-VN938		3/8" BSP	9	33
	-	DY-VN945		M14x1,5	9	33
	-	DY-VN965		M16x1,5	9	33
	-	DY-VN812	80	1/2" BSP	13	51
	-	DY-VN834		3/4" BSP	13	51
-	DY-VN824	M24x1,5		13	51	

Vsvuka s trnem na hadici 	index (s ventilem)	index (bez ventilu)	série	vnitř. průměr hadice [mm]	světlost [mm]	L [mm]
	-	DY-N624	6	6,3	4	35
	-	DY-N625		8	6	40
	-	DY-N626		9,5	6	40
	-	DY-N628		12,7	6	40
	-	DY-N926	90	9,5	7	41
	-	DY-N928		12,7	9	41
	-	DY-N828	80	12,7	10	53
-	DY-N819	19		13	62	

Vsvuka s koncovkou na zářežný prsteneč 	index (s ventilem)	index (bez ventilu)	série	vněj. průměr trubky [mm]	světlost [mm]
	-	DY-N614-K8	6	8	6
	-	DY-N638-K10		10	6
	-	DY-N914-K8	90	8	9
-	DY-N938-K10	10		9	