




Litínové adaptéry typ EE


Materiál: Tažná litina typ W 40-05 dle EN 1562 a 2000
Prac. teplota: Do +300°C
Prac. tlak: 25 bar (do +120°C), 20 bar (do +300°C)


Oblouk dlouhý 90°, vnitř. závit BSP / vněj. závit BSPT		
		
1/13		
index	DN	rozměr závitu [coul]
EE-113-04	8	1/4
EE-113-06	10	3/8
EE-113-08	15	1/2
EE-113-12	20	3/4
EE-113-16	25	1
EE-113-20	32	1.1/4
EE-113-24	40	1.1/2
EE-113-32	50	2
EE-113-40	65	2.1/2
EE-113-48	80	3
EE-113-64	100	4

Oblouk dlouhý 90°, vnitřní závit BSP		
		
2/15		
index	DN	rozměr závitu [coul]
EE-215-04	8	1/4
EE-215-06	10	3/8
EE-215-08	15	1/2
EE-215-12	20	3/4
EE-215-16	25	1
EE-215-20	32	1.1/4
EE-215-24	40	1.1/2
EE-215-32	50	2
EE-215-40	65	2.1/2
EE-215-48	80	3
EE-215-64	100	4

Oblouk dlouhý 45°, vnitř. závit BSP / vněj. závit BSPT		
		
40/22		
index	DN	rozměr závitu [coul]
EE-4022-04	8	1/4
EE-4022-06	10	3/8
EE-4022-08	15	1/2
EE-4022-12	20	3/4
EE-4022-16	25	1
EE-4022-20	32	1.1/4
EE-4022-24	40	1.1/2
EE-4022-32	50	2
EE-4022-40	65	2.1/2
EE-4022-48	80	3
EE-4022-64	100	4

Oblouk dlouhý 45°, vnitřní závit BSP		
		
41/20		
index	DN	rozměr závitu [coul]
EE-4120-06	8	1/4
EE-4120-08	10	3/8
EE-4120-12	15	1/2
EE-4120-16	20	3/4
EE-4120-20	25	1
EE-4120-24	32	1.1/4
EE-4120-32	40	1.1/2
EE-4120-40	50	2
EE-4120-48	65	2.1/2

Koleno 45°, vnitřní závit BSP		
		
120/5		
index	DN	rozměr závitu [coul]
EE-1205-08	15	1/2
EE-1205-12	20	3/4
EE-1205-16	25	1

T-kus 45°, vnitřní závit BSP		
		
165/30		
index	DN	rozměr závitu [coul]
EE-16530-08	15	1/2
EE-16530-12	20	3/4
EE-16530-16	25	1
EE-16530-20	32	1.1/4
EE-16530-24	40	1.1/2
EE-16530-32	50	2