




Rychlospojky TST - série 059, 060, 090, 190

Vsuвка a vnějším závitem L=100	index (s ventilem)	index (bez ventilu)	série	rozměr závitu	d1 [mm]	d2 [mm]	SW [mm]	L1 [mm]
		-		FW-060-BLM10-100	060	M10x1	6	9
	-	FW-060-BL10-100	1/8" BSP	6		9	11	40
	-	FW-060-BL13-100	1/4" BSP	6		9	14	40
	-	FW-060-BLM14-100	M14x1,5	6		9	14	40
	-	FW-060-BL17-100	3/8" BSP	6		9	17	40
	-	FW-090-BLM10-100	090	M10x1	9	13,5	14	40
	-	FW-090-BL10-100		1/8" BSP	9	13,5	14	40
	-	FW-090-BL13-100		1/4" BSP	9	13,5	14	40
	-	FW-090-BLM14-100		M14x1,5	9	13,5	14	40
	-	FW-090-BLM16-100		M16x1,5	9	13,5	17	40
	-	FW-090-BL17-100		3/8" BSP	9	13,5	17	40

Vsuвка s trubkou a vnějším závitem	index (s ventilem)	index* (bez ventilu)	série	rozměr závitu	d1 [mm]	d2 [mm]	SW [mm]	L1 [mm]	L [mm]
		-		FW-060-EUM8-L	060	M8x0,75	5	9	11
	-	FW-060-EUM10-L	M10x1	6		9	11	7	60/100/150
	-	FW-060-EU10-L	1/8" BSP	6		9	11	7	60/100/150
	-	FW-060-EU13-L	1/4" BSP	6		9	14	9	60/100/150
	-	FW-060-EUM14-L	M14x1,5	6		9	15	10	60/100/150
	-	FW-060-EU17-L	3/8" BSP	6		9	17	9	60/100/150
	-	FW-090-EU10-L	090	1/8" BSP	9	13,5	14	7	50/100/150
	-	FW-090-EUM12-L		M12x1,5	9	13,5	14	10	60/100/150
	-	FW-090-EU13-L		1/4" BSP	9	13,5	14	9	60/100/150
	-	FW-090-EUM14-L		M14x1,5	9	13,5	15	10	60/100/150
	-	FW-090-EUM16-L		M16x1,5	9	13,5	17	13	60/100/150
	-	FW-090-EU17-L		3/8" BSP	9	13,5	17	9	60/100/150
	-	FW-090-EU21-L	1/2" BSP	9	13,5	21	12	60/100/150	
	-	FW-190-EU21-L	190	1/2" BSP	13	19	22	12	60/100/150
	-	FW-190-EUM24-L		M24x1,5	13	19	27	15	60/100/250
	-	FW-190-EU26-L		3/4" BSP	13	19	27	16	60/100/150

* - Příkladový index vsuvky o délce 60 mm: FW-060-EUM8-060

Vsuвка s trubkou, bez závitů	index (s ventilem)	index (bez ventilu)	série	d [mm]	d1 [mm]	d2 [mm]	SW [mm]	L [mm]	L1 [mm]
		-		FW-060-BU063	060	8	6	9	9
	-	FW-060-BU100	10	6		9	11	100	21
	-	FW-060-BU120	10	6		9	11	120	21
	-	FW-060-BU240	10	6		9	11	240	21
	-	FW-060-BU360	10	6		9	11	360	21
	-	FW-090-BU150	090	14	9	13,5	15	150	22
	-	FW-090-BU300		14	9	13,5	15	300	22
	-	FW-090-BU450		14	9	13,5	15	450	22
	-	FW-190-BU500	190	21	13	19	22	500	35
	-	FW-190-BU800		21	13	19	22	800	35