

Přesné závitové spojky - mufny

velikost závitů	NPT vnitřní mufna				BSPT vnitřní mufna			BSP vnitřní mufna		
T [palec]	D [mm]	index (AISI 316)	L [mm]	V [palec]	index (AISI 316)	L [mm]	V [palec]	index (AISI 316)	L [mm]	V [palec]
1/8	7.8	HM-P103H-02-SS	20.6	9/16	HM-P103HR-02-SS	20.6	9/16	-	-	-
1/4	10.5	HM-P103H-04-SS	30.2	3/4	HM-P103HR-04-SS	30.2	3/4	HM-P103HG-04-SS	30.2	3/4
3/8	14.2	HM-P103H-06-SS	33.3	7/8	-	-	-	HM-P103HG-06-SS	33.3	7/8
1/2	17.4	HM-P103H-08-SS	39.6	1.1 / 16	HM-P103HR-08-SS	39.6	1.1 / 16	HM-P103HG-08-SS	39.6	1.1 / 16
3/4	22.9	HM-P103H-12-SS	41.1	1,5 / 16	HM-P103HR-12-SS	41.1	1,5 / 16	-	-	-
1	28.7	HM-P103H-16-SS	50.8	1,5 / 8	HM-P103HR-16-SS	50.8	1,5 / 8	-	-	-

velikost závitů	Redukční mufna GW NPT				
T [palec]	T ₁ [palec]	index (AISI 316)	L [mm]	D [mm]	V [palec]
1/4	1/8	HM-P119H-04-02-SS	31.0	7.8	3/4
3/8	1/8	HM-P119H-06-02-SS	~	7.8	7/8
3/8	1/4	HM-P119H-06-04-SS	35.1	10.5	7/8
1/2	1/8	HM-P119H-08-02-SS	39.6	7.8	1.1 / 16
1/2	1/4	HM-P119H-08-04-SS	44.5	10.5	1.1 / 16
1/2	3/8	HM-P119H-08-06-SS	45.2	14.2	1.1 / 16
3/4	1/4	HM-P119H-12-04-SS	46.0	10.5	1,5 / 16
3/4	3/8	HM-P119H-12-06-SS	~	14.2	1,5 / 16
3/4	1/2	HM-P119H-12-08-SS	52.3	17.4	1,5 / 16
1	1/4	HM-P119H-16-04-SS	~	10.5	1,5 / 8
1	1/2	HM-P119H-16-08-SS	55.6	17.4	1,5 / 8
1	3/4	HM-P119H-16-12-SS	57.2	22.9	1,5 / 8

Přesné šroubení - hadicové koncovky (1)

velikost trubky	vnitřní průměr hadice	Metrické hadicové koncovky							
B [mm]	[palec]	index (AISI 316)	L [mm]	F [mm]	I [mm]	C [mm]	D [mm]	D ₁ [mm]	V [palec]
6	1/4	HM-P130LTM-06-04-SS	47.2	20.1	15.7	7,62	4,80	4	7/16
10	1/4	HM-P130LTM-10-04-SS	~	20.1	~	7,62	4,80	~	~
10	3/8	HM-P130LTM-10-06-SS	~	22.1	~	11,43	7,60	~	~
10	1/2	HM-P130LTM-10-08-SS	~	23.9	~	15,24	9,70	~	~
12	3/8	HM-P130LTM-12-06-SS	~	22.1	~	11,43	7,60	~	~
12	1/2	HM-P130LTM-12-08-SS	~	23.9	~	15,24	9,70	~	~