




Přípojky SAE J1453 (ORFS)

popis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]	G [BSP]
			[mm]	[coul]		
Přípojka úhlová, stavitelná, vnitřní závit BSP  GAI-B	630	HO-GAI-09-B-04*	6	1/4	9/16-18	1/4
		HO-GAI-11-B-04*	8-10	5/16-3/8	11/16-16	1/4
		HO-GAI-13-B-04*	12	1/2	13/16-16	1/4
		HO-GAI-13-B-06*	12	1/2	13/16-16	3/8
	420	HO-GAI-16-B-08*	14-15-16	5/8	1-14	1/2
		HO-GAI-19-B-08*	18-20	3/4	1.3/16-12	1/2
		HO-GAI-19-B-12*	18-20	3/4	1.3/16-12	3/4
		HO-GAI-23-B-16*	22-25	7/8-1	1.7/16-12	1
	280	HO-GAI-27-B-20*	28-30-32	1.1/4	1.11/16-12	1.1/4
		HO-GAI-32-B-24*	35-38	1.1/2	2-12	1.1/2

popis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]	P [NPT]
			[mm]	[coul]		
Přípojka úhlová, stavitelná, vnitřní závit NPT  GAI-N	630	HO-GAI-09-N-04*	6	1/4	9/16-18	1/4
		HO-GAI-11-N-04*	8-10	5/16-3/8	11/16-16	1/4
		HO-GAI-13-N-04*	12	1/2	13/16-16	1/4
		HO-GAI-13-N-06*	12	1/2	13/16-16	3/8
	420	HO-GAI-16-N-08*	14-15-16	5/8	1-14	1/2
		HO-GAI-19-N-08*	18-20	3/4	1.3/16-12	1/2
		HO-GAI-19-N-12*	18-20	3/4	1.3/16-12	3/4
		HO-GAI-23-N-16*	22-25	7/8-1	1.7/16-12	1
	280	HO-GAI-27-N-20*	28-30-32	1.1/4	1.11/16-12	1.1/4
		HO-GAI-32-N-24*	35-38	1.1/2	2-12	1.1/2

popis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]	G [BSP]
			[mm]	[coul]		
Manometrová přípojka, GZ (ORFS) / GW BSP  MAV-B	400	HO-MAV-09-B-04	6	1/4	9/16-18	1/4
		HO-MAV-09-B-08	6	1/4	9/16-18	1/2
		HO-MAV-11-B-04	8-10	5/16-3/8	11/16-16	1/4
		HO-MAV-11-B-08	8-10	5/16-3/8	11/16-16	1/2
		HO-MAV-13-B-08	12	1/2	13/16-16	1/2

* - dostupné z nerezí AISI 316