





Spojky SAE J1453 (ORFS)

popis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]
			[mm]	[coul]	
T-kus  T	630	HO-T-09	6	1/4	9/16-18
		HO-T-11	8-10	5/16-3/8	11/16-16
		HO-T-13	12	1/2	13/16-16
	420	HO-T-16	14-15-16	5/8	1-14
		HO-T-19	18-20	3/4	1.3/16-12
		HO-T-23	22-25	7/8-1	1.7/16-12
	280	HO-T-27	28-30-32	1.1/4	1.11/16-12
		HO-T-32	35-38	1.1/2	2-12

opis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]
			[mm]	[coul]	
T-kus, stavitelný, asymetrický  EVL	630	HO-EVL-09*	6	1/4	9/16-18
		HO-EVL-11*	8-10	5/16-3/8	11/16-16
		HO-EVL-13*	12	1/2	13/16-16
	420	HO-EVL-16*	14-15-16	5/8	1-14
		HO-EVL-19*	18-20	3/4	1.3/16-12
		HO-EVL-23*	22-25	7/8-1	1.7/16-12
	280	HO-EVL-27*	28-30-32	1.1/4	1.11/16-12
		HO-EVL-32*	35-38	1.1/2	2-12

popis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]
			[mm]	[coul]	
Zátka s vněj. závitem ORFS  ROV	630	HO-ROV-09*	6	1/4	9/16-18
		HO-ROV-11*	8-10	5/16-3/8	11/16-16
		HO-ROV-13*	12	1/2	13/16-16
	420	HO-ROV-16*	14-15-16	5/8	1-14
		HO-ROV-19*	18-20	3/4	1.3/16-12
		HO-ROV-23*	22-25	7/8-1	1.7/16-12
	280	HO-ROV-27*	28-30-32	1.1/4	1.11/16-12
		HO-ROV-32*	35-38	1.1/2	2-12

popis	tlak [bar]	index	smluvní vnější průměr trubky		ORFS [UN-UNF]
			[mm]	[coul]	
Zátka s vnitř. závitem  VKA	630	HO-VKA-09*	6	1/4	9/16-18
		HO-VKA-11*	8-10	5/16-3/8	11/16-16
		HO-VKA-13*	12	1/2	13/16-16
	420	HO-VKA-16*	14-15-16	5/8	1-14
		HO-VKA-19*	18-20	3/4	1.3/16-12
		HO-VKA-23*	22-25	7/8-1	1.7/16-12
	280	HO-VKA-27*	28-30-32	1.1/4	1.11/16-12
		HO-VKA-32*	35-38	1.1/2	2-12

* - dostupné z nerezí AISI 316