




Spojky pro odsávací hadice

Koleno 45° (R = 1,5xd)		
		
KSBB 45		
index	DN	vnější průměr [mm]
KS-KSBB45-080-OC	80	77
KS-KSBB45-100-OC	100	97
KS-KSBB45-125-OC	125	122
KS-KSBB45-140-OC	140	137
KS-KSBB45-150-OC	150	147
KS-KSBB45-160-OC	160	157
KS-KSBB45-180-OC	180	177
KS-KSBB45-200-OC	200	197
KS-KSBB45-225-OC	225	222
KS-KSBB45-250-OC	250	247
KS-KSBB45-280-OC	280	277
KS-KSBB45-300-OC	300	297
KS-KSBB45-400-OC	400	397
KS-KSBB45-500-OC	500	497

T-kus Y		
		
KTSBY		
index	DN	vnější průměr [mm]
KS-KTSBY-100-OC	100	97
KS-KTSBY-125-OC	125	122
KS-KTSBY-140-OC	140	137
KS-KTSBY-150-OC	150	147
KS-KTSBY-160-OC	160	157
KS-KTSBY-180-OC	180	177
KS-KTSBY-200-OC	200	197
KS-KTSBY-225-OC	225	222
KS-KTSBY-250-OC	250	247
KS-KTSBY-280-OC	280	277
KS-KTSBY-300-OC	300	297
KS-KTSBY-400-OC	400	397
KS-KTSBY-500-OC	500	497

T-kus symetrický 90°		
		
KTSB 90		
index	DN	vnější průměr [mm]
KS-KTSB90-080-OC	80	77
KS-KTSB90-100-OC	100	97
KS-KTSB90-125-OC	125	122
KS-KTSB90-140-OC	140	137
KS-KTSB90-150-OC	150	147
KS-KTSB90-160-OC	160	157
KS-KTSB90-180-OC	180	177
KS-KTSB90-200-OC	200	197
KS-KTSB90-225-OC	225	222
KS-KTSB90-250-OC	250	247
KS-KTSB90-280-OC	280	277
KS-KTSB90-300-OC	300	297
KS-KTSB90-400-OC	400	397
KS-KTSB90-500-OC	500	497

T-kus asymetrický 45°		
		
KTSB 45		
index	DN	vnější průměr [mm]
KS-KTSB45-080-OC	80	77
KS-KTSB45-100-OC	100	97
KS-KTSB45-125-OC	125	122
KS-KTSB45-140-OC	140	137
KS-KTSB45-150-OC	150	147
KS-KTSB45-160-OC	160	157
KS-KTSB45-180-OC	180	177
KS-KTSB45-200-OC	200	197
KS-KTSB45-225-OC	225	222
KS-KTSB45-250-OC	250	247
KS-KTSB45-280-OC	280	277
KS-KTSB45-300-OC	300	297
KS-KTSB45-400-OC	400	397
KS-KTSB45-500-OC	500	497