






**Systém pro chlazení LOC-LINE®**
**Hadice s tryskou a ventilem**

systém	index	vnitřní průměr [coul]	délka [mm]	přípojka [coul]	průměr trysky [coul]	tlak [bar]	maximální průtok [l/hod]
1/4"	LL-P0413Z	1/4"	400	GZ 1/4" NPT	1/4"	2÷3	1136
	LL-P0513Z	1/4"	500	GZ 1/4" NPT	1/4"	2÷3	1136
	LL-P0613Z	1/4"	600	GZ 1/4" NPT	1/4"	2÷3	1136
1/2"	LL-P1412Z	1/2"	400	GZ 1/2" NPT	1/2"	1,4÷2	2173
	LL-P1512Z	1/2"	500	GZ 1/2" NPT	1/2"	1,4÷2	2173
	LL-P1612Z	1/2"	600	GZ 1/2" NPT	1/2"	1,4÷2	2173
3/4"	LL-P2402Z	3/4"	400	GZ 3/4" NPT	3/4"	0,7÷1,4	5182
	LL-P2501Z	3/4"	500	GZ 3/4" NPT	3/4"	0,7÷1,4	5182
	LL-P2601Z	3/4"	600	GZ 3/4" NPT	3/4"	0,7÷1,4	5182


**Elementy hadic pro chlazení LOC-LINE®**

obrázek	popis	index		
		systém 1/4"	systém 1/2"	systém 3/4"
	Hadice <sup>1)</sup>	LL-41401 (L=2x145 mm)	LL-51801 (L=2x140 mm)	LL-61501 (L=2x145 mm)
	Role hadice	LL-49421 (L = 15,20 m)	LL-59861 (L = 15,20 m)	LL-69541 (L = 15,20 m)
	Prodloužení	LL-49445 (L = 90 mm)	LL-59883 (L = 89,50 mm)	-
	Prodloužení 90°	LL-49457	LL-59899	-
	Upevňovací objímka	LL-49446	LL-59884	-

1) dostupné jiné délky 100 mm, 200 mm... do 1000 mm, příkladový index hadice 1/4" o délce 500 mm: LL-P00500