

Symetrické spojky STORZ



Záslepka

Materiál: hliník (Al), mosaz (Ms),
nerez (SS)
Prac. tlak: 16 bar
Těsnění: bílá pryž NBR pro hliník,
černá pryž NBR pro mosaz,
viton pro nerez

index (hliník)	index (mosaz)	index (nerez)	rozměr	rozteč západek KA [mm]
ST-31-031000-11	ST-31-031000-30	ST-31-031000-43	25-D	31
ST-31-044000-11	ST-31-044000-30	-	32	44
ST-31-051000-11	ST-31-051000-30	ST-31-051000-43	38	51
ST-31-059000-11	-	-	45	59
ST-31-066000-11	ST-31-066000-30	ST-31-066000-43	52-C	66
ST-31-066000-21*	-	-		
ST-31-081000-11	ST-31-081000-30	ST-31-081000-43	65	81
ST-31-089000-11	ST-31-089000-30	ST-31-089000-43	75-B	89
ST-31-089000-21*	-	-		
ST-31-105000-11	-	-	90	105
ST-31-115000-11	ST-31-115000-30	ST-31-115000-43	100	115
ST-31-133000-11	ST-31-133000-30	ST-31-133000-43	110-A	133
ST-31-133000-21*	-	-		
ST-31-148000-11	ST-31-148000-30	ST-31-148000-43	125	148
ST-31-160000-11	ST-31-160000-30	ST-31-160000-43	150	160
ST-31-220000-11**	-	-	205	220
ST-31-278000-11**	-	-	250	278

* - odlévaná verze PN 6 bar
** - PN 10 bar



Plastová záslepka

Materiál korpusu: vysoce odolný plast
Materiál víčka: hliník (Al)
Prac. tlak: 10 bar
Těsnění: černá pryž NBR

index	rozměr	rozteč západek KA [mm]
ST-31-066000-60	52-C	66