

## Symetrické spojky STORZ



### Redukce

**Materiál:** hliník (Al), mosaz (Ms),  
 nerez (SS)  
**Prac. tlak:** 16 bar  
**Těsnění:** bílá pryž NBR pro hliník,  
 černá pryž NBR pro mosaz,  
 viton pro nerez

index (hliník)	index (mosaz)	index (nerez)	rozměr	rozteč západek KA [mm]
ST-35-031100-11	-	-	25-D / Geka	31 / 40
ST-35-051031-11	-	-	38 / 25-D	51 / 31
ST-35-059031-11	-	-	45 / 25-D	59 / 31
ST-35-066100-11	-	-	52-C / Geka	66 / 40
ST-35-066031-11	ST-35-066031-30	ST-35-066031-43	52-C / 25-D	66 / 31
ST-35-066044-11	ST-35-066044-30	-	52-C / 32	66 / 44
ST-35-066051-11	ST-35-066051-30	-	52-C / 38	66 / 51
ST-35-081051-11	-	-	65 / 38	81 / 51
ST-35-081059-11	-	-	65 / 45	81 / 59
ST-35-081066-11	ST-35-081066-30	ST-35-081066-43	65 / 52-C	81 / 66
ST-35-089066-11	ST-35-089066-30	ST-35-089066-43	75-B / 52-C	89 / 66
ST-35-089066-21*	-	-		
ST-35-089081-11	ST-35-089081-30	ST-35-089081-43	75-B / 65	89 / 81
ST-35-105089-11	-	-	90 / 75-B	105 / 89
ST-35-115081-11	-	-	100 / 65	115 / 81
ST-35-115089-11	-	-	100 / 75-B	115 / 89
ST-35-115105-11	-	-	100 / 90	115 / 105
ST-35-133066-11	-	-	110-A / 52-C	133 / 66
ST-35-133081-11	-	-	110-A / 65	133 / 81
ST-35-133089-11	ST-35-133089-30	ST-35-133089-43	110-A / 75-B	133 / 89
ST-35-133089-21*	-	-		
ST-35-133105-11	-	-	110-A / 90	133 / 105
ST-35-133115-11	-	-	110-A / 100	133 / 115
ST-35-148115-11	-	-	125 / 100	148 / 115
ST-35-148133-11	-	-	125 / 110-A	148 / 133
ST-35-160115-11	-	-	150 / 100	160 / 115
ST-35-160133-11	-	-	150 / 110-A	160 / 133
ST-35-160148-11	-	-	150 / 125	160 / 148
ST-35-188133-11**	-	-	165 / 110-A	188 / 133
ST-35-188160-11**	-	-	165 / 150	188 / 160
ST-35-220160-11**	-	-	205 / 150	220 / 160
ST-35-278220-11**	-	-	250 / 205	278 / 220

\* - odlévaná verze PN 6 bar

\*\* - PN 10 bar