

Symetrické spojky STORZ


Nastavitelná proudnice		
		
index (hliník)	rozměr [coul]	přípojka (vstup)
ST-46-200000-10	2	GZ 2" BSP
ST-46-200066-10		52-C
ST-46-250000-10	2.1/2	GZ 2.1/2" BSP
ST-46-250089-10		75-B

Nastavitelná proudnice		
		
index (polyamid)	rozměr [coul]	přípojka (vstup)
ST-47-100000-90	1	GZ 1" BSP
ST-47-100031-90		25-D
ST-47-100025-90		pro hadice 25 mm

Záslepka s odpouštěcím ventilem		
		
index (hliník)	rozměr	rozteč západek [mm]
ST-31-600066-11	52-C	66
ST-31-600081-11	65	81
ST-31-600089-11	75-B	89
ST-31-600105-11	90	105
ST-31-600115-11	100	115
ST-31-600133-11	110-A	133
ST-31-600148-11	125	148
ST-31-600160-11	150	160

Hydrantová záslepka pro trojhranný klíč			
			
index (hliník)	rozměr	rozteč západek [mm]	rozměr závitů
ST-32-066000-10	52-C	66	Rd 50x1/6"
ST-32-081000-10	65	81	Rd 60x1/6"
ST-32-089000-10	75-B	89	Rd 65x1/6"
ST-32-133000-10	110-A	133	Rd 105x1/4"

Řetízek k záslepce		
		
index (pozinkovaná ocel)	index (nerez)	rozměr
ST-91-006031-50	ST-91-006031-70	25-D do 38
ST-91-006066-50	ST-91-006066-70	45 do 75-B
ST-91-006133-50	ST-91-006133-70	90 do 150
ST-91-006220-50	-	165 do 205
ST-91-006500-50*	ST-91-006500-70*	-

Ploché těsnění pro hydrantové záslepky		
		
index (černá NBR)	rozměr	rozměry [mm]
ST-91-004066-00	52-C	58 x 46 x 4
ST-91-004081-00	65	75 x 54 x 3
ST-91-004089-00	75-B	78 x 61 x 4
ST-91-004133-00	110-A	119 x 100 x 4

* - pro hydrantové záslepky (ST-32)