







Těsnění



Profilové těsnění dle DIN 3869

Těsnění NBR	Těsnění viton	Těsnění dle DIN 3869			Přípojka dle DIN 3852-11E	
 UE	 UE-V					
index (NBR85)*	index (viton80)*	d [mm]	D [mm]	s [mm]	metrický závit	palcový závit
TI-UE-08	TI-UE-08-V	6,5	9,9	1	8x1	-
TI-UE-10	TI-UE-10-V	8,4	11,9	1	10x1	1/8 BSP
TI-UE-12	TI-UE-12-V	9,8	14,4	1,5	12x1,5	-
TI-UE-14	TI-UE-14-V	11,6	16,5	1,5	14x1,5	1/4 BSP
TI-UE-16	TI-UE-16-V	13,8	18,9	1,5	16x1,5	-
TI-UE-17	TI-UE-17-V	14,7	18,9	1,5	-	3/8 BSP
TI-UE-18	TI-UE-18-V	15,7	20,9	1,5	18x1,5	-
TI-UE-20	TI-UE-20-V	17,8	22,9	1,5	20x1,5	-
TI-UE-21	TI-UE-21-V	18,5	23,9	1,5	-	1/2 BSP
TI-UE-22	TI-UE-22-V	19,6	24,3	1,5	22x1,5	-
TI-UE-26	TI-UE-26-V	23,9	29,2	1,5	26x1,5 / 27x2	3/4 BSP
TI-UE-33	TI-UE-33-V	29,7	35,7	2	33x2	1 BSP
TI-UE-42	TI-UE-42-V	38,8	45,8	2	42x2	1.1/4 BSP
TI-UE-48	TI-UE-48-V	44,7	50,7	2	48x2	1.1/2 BSP

* - přípustná pracovní teplota od -30°C do +100°C (NBR) nebo od -20°C do +200°C (viton)

Těsnění ploché

Měděné těsnění					
					UM
index	rozměr		rozměry [mm]		
	[mm]	[coul]	d	D	s
TI-UM-06-10	6	-	6	10	1,5
TI-UM-08-12	8	-	8	12	1,5
TI-UM-08-14	8	-	8	14	1,5
TI-UM-10-14	10	1/8	10	14	1,5
TI-UM-10-16	10	1/8	10	16	1,5
TI-UM-12-15	12	-	12	15	1,5
TI-UM-12-18	12	-	12	18	1,5
TI-UM-13-19	13	1/4	13	19	1,5
TI-UM-14-20	14	-	14	20	1,5
TI-UM-16-22	16	-	16	22	1,5
TI-UM-17-21	17	3/8	17	21	1,5
TI-UM-18-24	18	-	18	24	1,5
TI-UM-20-26	20	-	20	26	1,5
TI-UM-21-26	21	1/2	21	26	1,5
TI-UM-22-27	22	-	22	27	1,5
TI-UM-24-30	24	5/8	24	30	1,5
TI-UM-26-33	26	-	26	33	1,5
TI-UM-27-33	27	3/4	27	33	1,5
TI-UM-30-36	30	-	30	36	1,5
TI-UM-33-40	33	1	33	40	1,5
TI-UM-42-49	42	1.1/4	42	49	1,5
TI-UM-48-59	48	1.1/2	48	59	1,5

Teflonové těsnění (PTFE)					
					UBW140
index	rozměr [coul]	rozměry [mm]			
		d	D	s	
TI-UBW140-04-T	1/4	6	11,3	2	
TI-UBW140-06-T	3/8	7	15	2	
TI-UBW140-08-T	1/2	10	19	2	
TI-UBW140-12-T	3/4	12	24	2	
TI-UBW140-16-T	1	20	30	2	
TI-UBW140-20-T	1.1/4	28	38	2	
TI-UBW140-24-T	1.1/2	34	44,5	2	
TI-UBW140-32-T	2	42,5	56,2	3	
TI-UBW140-40-T	2.1/2	55,5	72	3	
TI-UBW140-04-TN	1/4	6	11,5	2	
TI-UBW140-06-TN	3/8	9	15	2	
TI-UBW140-08-TN	1/2	11,5	18,7	2	
TI-UBW140-12-TN	3/4	16,5	24,2	2	
TI-UBW140-16-TN	1	22	31	2	
TI-UBW140-20-TN	1.1/4	28	39,5	2	
TI-UBW140-24-TN	1.1/2	34	45,5	2	
TI-UBW140-32-TN	2	46	57	3	