

Přírubové spoje - příruby EN1092-1 PN16

Materiál: uhlíková ocel, nerez 304 (k indexu přidat SS), nerez 316 (k indexu přidat SS316).

DN	index					
	typ 01B	typ 32B	typ 02	typ 11B	typ 34B	typ 04
15	TK-KSP-015	TK-KOPP-015	TK-KO-T02-015	TK-KSS-015	TK-KOPS-015	TK-KO-015
20	TK-KSP-020	TK-KOPP-020	TK-KO-T02-020	TK-KSS-020	TK-KOPS-020	TK-KO-020
25	TK-KSP-025	TK-KOPP-025	TK-KO-T02-025	TK-KSS-025	TK-KOPS-025	TK-KO-025
32	TK-KSP-032	TK-KOPP-032	TK-KO-T02-032	TK-KSS-032	TK-KOPS-032	TK-KO-032
40	TK-KSP-040	TK-KOPP-040	TK-KO-T02-040	TK-KSS-040	TK-KOPS-040	TK-KO-040
50	TK-KSP-050	TK-KOPP-050	TK-KO-T02-050	TK-KSS-050	TK-KOPS-050	TK-KO-050
65	TK-KSP-065	TK-KOPP-065	TK-KO-T02-065	TK-KSS-065	TK-KOPS-065	TK-KO-065
80	TK-KSP-080	TK-KOPP-080	TK-KO-T02-080	TK-KSS-080	TK-KOPS-080	TK-KO-080
100	TK-KSP-100	TK-KOPP-100	TK-KO-T02-100	TK-KSS-100	TK-KOPS-100	TK-KO-100
125	TK-KSP-125	TK-KOPP-125	TK-KO-T02-125	TK-KSS-125	TK-KOPS-125	TK-KO-125
150	TK-KSP-150	TK-KOPP-150	TK-KO-T02-150	TK-KSS-150	TK-KOPS-150	TK-KO-150

Hadicevé trny pro přivaření na příruby

DN	index	vnitřní prům. hadice [mm]	d [mm]	typ
25	TK-WC-025	25	33,7	A
32	TK-WC-032	32	42,4	A
40	TK-WC-040	38-40	48,3	A
50	TK-WC-050	50-51	60,3	A
65	TK-WC-065	63-65	76,1	A
80	TK-WC-080-076	75-76	88,9	A
80	TK-WC-080-080	80	88,9	A
100	TK-WC-100	100-102	114,3	B
125	TK-WC-125	125-127	139,7	B
150	TK-WC-150	150-152	168,3	B
200	TK-WC-200	200-203	219,1	C
250	TK-WC-250	250-254	273,0	C

DN	index	vnitřní prům. hadice [mm]	d [mm]
15	TK-WRS-015-013	13	21,3
20	TK-WRS-020-019	19	26,9
25	TK-WRS-025-025	25	33,7
32	TK-WRS-032-032	32	42,4
40	TK-WRS-040-038	38	48,3
40	TK-WRS-040-040	40	48,3
50	TK-WRS-050-050	50	60,3
50	TK-WRS-050-051	51	60,3
65	TK-WRS-065-063	63	76,1
65	TK-WRS-065-065	65	76,1
80	TK-WRS-080-076	76	88,9
80	TK-WRS-080-080	80	88,9
100	TK-WRS-100-100	100	114,3
100	TK-WRS-100-102	102	114,3
125	TK-WRS-125-125	125	139,7
125	TK-WRS-125-127	127	139,7
150	TK-WRS-150-150	150	168,3
150	TK-WRS-150-152	152	168,3
200	TK-WRS-200-200	200	219,1
200	TK-WRS-200-203	203	219,1

Materiál: uhlíková ocel, nerez 304 (k indexu přidat SS), nerez 316 (k indexu přidat SS316).

Pracovní tlak 10 bar (typ TK-WC), 25 bar (typ TK-WRS).

- pro montáž sponami (typ TK-WC),
- pro montáž objímkami RS nebo pro zalisování objímkami TI-LR, TI-LDR (typ TK-WRS).